



bizhub C252

CONNECT

COMMUNICATE

CONTROL



General Specifications:

TYPE:
Full-Color Printer/Copier/Scanner With Stationary Platen

PRINT/COPY PROCESS:
Tandem Process

IMAGING SYSTEM:
Simitri® Color Polymerized Toner
Error Diffusion Method

MONTHLY DUTY CYCLE:
75,000 pages

PRINT/COPY SPEED:
Full Color and B&W: 25 ppm (letter, portrait)

COPY RESOLUTION:
600 x 600 dpi

PRINT RESOLUTION:
600 x 600 dpi

SCAN SPEED:
Up to 25 opm

SCAN RESOLUTION:
600 x 600, 400 x 400, 300 x 300,
200 x 200 dpi

SCAN FILE FORMATS:
TIFF (MH, MMR), PDF (MH, MMR, JPEG),
Compact PDF, JPEG

MEMORY:
512 MB (standard/maximum)

HARD DISK DRIVE:
40 GB

GRADATION:
256 color shades per pixel

ORIGINAL SIZE:
Up to 11" x 17" (scanning/copying)
Up to 11" x 17" full-bleed on 12" x 18"
paper (printing)

COPY SIZE:
Multi-Purpose Cassette: 4" x 6" to
12" x 18"
Universal Cassette: 5-1/2" x 8-1/2" to
11" x 17"
Intelligent Multiple Bypass: 4" x 6" to 12" x 18"

WARM-UP TIME:
Less than 110 seconds

FIRST COPY:
Full color: less than 11.7 seconds (letter)
B&W: less than 8.4 seconds (letter)

COPY QUANTITY:
1 - 999

MAGNIFICATION:
Zoom range: 25% - 400%, 0.1%
increments
Preset reduction: 79%, 73%, 65%, 50%
Preset enlargement: 121%, 129%,
155%, 200%

COLOR MODES:
Auto Color, Full Color, Black & White,
2-Color, Single Color

COPY EXPOSURE MODES:
Text (legible text)
Text/Photo (clear text and halftones)
Photo (optimized for gradations)
Map (fine edges and legible text)
Dot Matrix (dot matrix originals)
Copied Paper

FAXING (optional):
Super G3 compatibility
33.6 Kbps modem speed (auto fallback
to 2,400 bps)

DATA COMPRESSION:
MH, MR, MMR, JBIG

FAX TRANSMISSION SPEED:
Less than 2 seconds/page
(JBIG, standard resolution)

FAX MEMORY:
32 MB

FAX EXPOSURE MODES:
Text, Text/Photo, Photo, Dot Matrix

STANDARD PAPER SUPPLY:
250-sheet multi-purpose cassette
(16 lb. bond to 140 lb. index)
500-sheet cassette
(16 lb. bond to 24 lb. bond)
100-sheet bypass
(16 lb. bond to 140 lb. index)

MAXIMUM PAPER CAPACITY:
3,350 sheets (total, with options)

DOCUMENT FEEDER:
DF-601 Automatic Document Feeder
(optional)
Speed: 25 opm
Paper Capacity: 100 sheets
Paper Size: 5-1/2" x 8-1/2" to 11" x 17"
Paper Weight: Single-sided:
10 lb. bond to 110 lb. index;
Double-sided: 13 lb. bond to 28 lb. bond

POWER REQUIREMENTS:
120 V, 60 Hz

POWER CONSUMPTION:
Less than 1.5 kW

DIMENSIONS (W x D x H):
C252: 25-1/2" x 29-3/4" x 30-1/4"
(standard configuration)

WEIGHT:
C252: 209-1/4 lbs.

OPTIONS:
DF-601 Reversing Automatic
Document Feeder
DK-502 Copy Desk
EK-702 Parallel/USB 2.0 I/F Kit
FK-502 Fax Kit
FS-514 Base Finisher
FS-603 Booklet Finisher
ML-501 Multi Line
MK-704 Fax Connection Kit
MK-706 Enhanced Option Connection
MT-501 Mail Bin Kit (for FS-514)
OC-501 Original Cover
OT-601 Output Tray (for FS-514)
PC-103 Paper Feed Cabinet
(500 sheets)
PC-203 Paper Feed Cabinet
(500 sheets x 2)
PC-403 Large Capacity Tray
(2,500 sheets)
PK-501 Punch Kit
(for FS-603 Booklet Finisher)
PK-501 Punch Kit (for FS-514)
SA-501 Scan Accelerator Kit
SC-503 HDD Encryption Kit
SD-503 Saddle Stitcher (for FS-514)

Available Print/Copy Functions*

Account Track (up to 1,000 accounts)
APS/AMS
Auto Duplex
Auto Reset
Auto Tray Switching
Bi-Directional Communication
(Device Option Setting)
B/W Public Access;
Password Protected Color Access
Color Modes & Functions:
Auto Color/Full Color
Black & White Mode
Single Color Mode
2-Color Mode
Color Adjustments (Brightness,
Contrast, Saturation, Sharpness,
Red, Green, Blue, Portrait, Hue Density,
Color Balance, Copy Density)
Sample Copy

Available Print/Copy Functions
Continued*

Copy Modes (Simplex/Duplex, 2-in-1, 4-in-1, 8-in-1, Book Separation, Booklet Creation, Catalog Binding)
Cover Mode
Creative Functions (Mirror Image, Image Repeat, XY Zoom, Image Centering, Base Color, Negative/Positive Reverse)
Criss-Cross Sorting
Distribution Number Printing
Duplexing (Standard)
Energy Save Mode
Enlarge Display
Erase (Frame, Book Frame, Book Center)
Finishing (Group, Sort, Staple, Punch, Booklet, Center-Fold, Center-Staple)
Form Overlay
HDD Random Erase
Image Adjustments (Color Matching, Pure Black Auto ON/OFF, Color Balance, Screen Setting, Image Smoothing ON/OFF)
Image Density Adjustment (Background: Manual/Auto; Density: Manual)
Image Preview (Job Finishing Image Display, Engine Configuration Display)
Interrupt
Job Erase
Job List
Job Reserve
LDAP/up to 5 LDAP Servers/Global LDAP
OHP Interleaving
Mixplex, Mix-Media
Paper Type Selection (Normal, Thick 1, Thick 2, Thick 3, OHP)
Program/Recall Jobs
Proof
Secure Printing
Separate Scan
Sleep Mode
Text Enhancement Adjustment
User Authentication (Synchronize with Account Track)
User Box Function (Store Copy Jobs/Print Jobs/Scans/Fax Data, Print Stored Data, Route Scanned Data, Print or Combine Scanned Data)
Utility (Meter Count, Environment Setting, Default Setting, One-Touch Setting, Check Consumable Life, Admin Mode)
Watermarks
Zoom Selection (AMS, Fixed Zoom Ratio, User Programmable Zoom Ratio, Manual)

Available Scan Functions*

Scan-to-Email
Scan-to-FTP
Scan-to-SMB (Scan-to-Desktop)
Scan-to-HDD (Scan-to-User Box)
Network TWAIN

Available Fax Functions*

Auto Dialing
Auto Memory Reception
Auto Reduction Printing
Border Erase Transmission
Broadcasting (maximum 600 locations)
Bulletin Board
Density Adjustment
Duplex Transmission/Reception
Exposure Mode (Text, Text/Photo, Photo, Dot Matrix)
Fax Forwarding
Image Rotation Transmission/Reception
Internet Faxing
IP Address Faxing
Mailbox (Private)
Transmission/Reception
Memory/Quick Dial
Memory Transmission/Reception
Mixed Originals Transmission
Multi Address Transmission
600 Addresses (maximum)
Original Size Designation
Overseas Transmission
Password Transmission/Reception
PC Fax (PCL driver only)
Polling Transmission/Reception
Priority Transmission
Program Dialing: 400 programs
Redial
Relay Broadcasting
Relay Transmission
Remote Reception
TSI User Box
TSI User Box Routing
Secure Printing
Timer Transmission

Emperon Print System

PROCESSOR:
466 MHz (PPC750FX)

RAM:
512 MB (standard)

HARD DISK DRIVE:
40 GB (standard copier memory)

PAGE DESCRIPTION LANGUAGE:

PCL 5e/5c Emulation
PCL6 (XL version 2.1) Emulation
PS3 Emulation

FONTS:

PCL Resident Fonts:
80 outline + 1 bitmap
PS3 Emulation Resident Fonts:
136 outline

PRINT DRIVERS:

PCL6: Windows 98SE, ME, 2000, XP, 2003, NT 4.0 SP6
PS3: Windows 98SE/ME (PPD file), 2000/XP/2003/NT 4.0 SP6 (Print Drivers), Windows 2003 64-BIT Driver
Mac OS 9.2 or later,
Mac OS X 10.2,
Mac OS X 10.3 (PPD files)
Mac OS x 10.4
TWAIN Driver: Windows 98SE, ME, 2000, XP, NT 4.0 SP6

INTERFACE:

Ethernet 10/100 BaseT
Parallel IEEE 1284 (optional)
USB 1.1, 2.0 (optional)

PROTOCOLS:

TCP/IP, IPX/SPX (NDS), SMB, NetBEUI, LPD, LPR, IPP 1.1, SNMP, HTTP, AppleTalk (EtherTalk), Pserver (Novell 4.x, 5, 6/NDS), NPrinter, NDPS, SMTP, POP3, LDAP, SSL

PAGESCOPE APPLICATIONS:

Network & Device Management (bundle):
PageScope Box Operator
PageScope Data Administrator
PageScope Direct Print
PageScope EMS Plug-Ins
PageScope Job Spooler
PageScope NDPS Gateway
PageScope Net Care
PageScope Network Setup
PageScope Print Status Notifier
PageScope Web Connection

OPTIONAL SOFTWARE:

PageScope Workware
PageScope Router

OTHER UTILITIES:

HDD Backup Tool*
Plug-in for HP Web JetAdmin*

* Some functions may require options, which may or may not be available at time of launch.



KONICA MINOLTA

KONICA MINOLTA
BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive
Rumsey, NJ 07446
www.kmbs.konicaminolta.us
www.kmbs.konicaminolta.us/solutions