











# **General Specifications:**

#### TYPE:

Full-Color Printer/Copier/Scanner With Stationary Platen

# PRINT/COPY PROCESS:

**Tandem Process** 

#### IMAGING SYSTEM:

Simitri® Color Polymerized Toner Error Diffusion Method

# MONTHLY DUTY CYCLE:

90,000 pages

# PRINT/COPY SPEED:

Full Color and B&W: 30 ppm (letter, portrait)

# COPY RESOLUTION:

600 x 600 dpi

# PRINT RESOLUTION:

1800 dpi Equivalent x 600 dpi

# SCAN SPEED:

Up to 65 opm (B&W); 50 opm (color)

# SCAN RESOLUTION:

600 x 600, 400 x 400, 300 x 300, 200 x 200 dpi

# SCAN FILE FORMATS:

TIFF (MH, MMR), PDF (MH, MMR, JPEG), Compact PDF, JPEG

#### MEMORY:

512 MB (standard/maximum)

# HARD DISK DRIVE:

40 GB

# GRADATION:

256 color shades per pixel

#### ORIGINAL SIZE:

Up to 11" x 17" (scanning/copying)
Up to 11" x 17" full-bleed on 12" x 18"
paper (printing)

#### COPY SIZE:

Multi-Purpose Cassette: 4" x 6" to 12" x 18" Universal Cassette: 5-1/2" x 8-1/2" to 11" x 17" Multiple Bypass: 4" x 6" to 12" x 18"

#### WARM-UP TIME:

Less than 72 seconds

#### FIRST COPY:

Full color: less than 8.5 seconds (letter) B&W: less than 6.5 seconds (letter)

#### COPY QUANTITY:

1 - 999

# MAGNIFICATION:

Zoom range: 25% - 400%, 0.1% increments
Preset reduction: 79%, 73%, 65%, 50%
Preset enlargement: 121%, 129%, 155%, 200%

#### COLOR MODES:

Auto Color, Full Color, Black & White, 2-Color, Single Color

# **COPY EXPOSURE MODES:**

Text (legible text)
Text/Photo (clear text and halftones)
Photo (optimized for gradations)
Map (fine edges and legible text)
Dot Matrix (dot matrix originals)
Copied Paper

# FAXING (optional):

Super G3 compatibility 33.6 Kbps modem speed (auto fallback to 2,400 bps)

# DATA COMPRESSION:

MH, MR, MMR, JBIG

# FAX TRANSMISSION SPEED:

Less than 2 seconds/page (JBIG, standard resolution)

#### FAX MEMORY:

32 MB

#### **FAX EXPOSURE MODES:**

Text, Text/Photo, Photo, Dot Matrix

# STANDARD PAPER SUPPLY:

250-sheet multi-purpose cassette (16 lb. bond to 140 lb. index) 500-sheet cassette (16 lb. bond to 24 lb. bond) 100-sheet bypass

# (16 lb. bond to 140 lb. index) MAXIMUM PAPER CAPACITY:

3,350 sheets (total, with options)

DF-608 Automatic Document Feeder

# **DOCUMENT FEEDER:**

(optional)
Speed: Up to 65 opm (B&W); 50 opm (color)
Paper Capacity: 100 sheets
Paper Size: 5-1/2" x 8-1/2" to 11" x 17"
Paper Weight: Single-sided:
9.25 lb. bond to 110 lb. index;
Double-sided: 16 lb. bond to 34 lb. bond

# POWER REQUIREMENTS:

120 V, 60 Hz

# POWER CONSUMPTION:

Less than 1.5 kW

# DIMENSIONS (W x D x H):

C300: 25-1/2" x 29-1/2" x 30-1/4" (standard configuration)

#### WEIGHT:

C300: 226 - 3/4 lbs.

#### OPTIONS:

Document Feeder DK-502 Copy Desk EK-702 Parallel/USB 2.0 I/F Kit FK-502 Fax Kit FS-514 Base Finisher MK-706 Enhanced Option Connection ML-501 Multi Line OC-501 Original Cover OT-601 Output Tray PC-103 Paper Feed Cabinet (500 sheets) PC-203 Paper Feed Cabinet (500 sheets x 2) PC-403 Large Capacity Tray (2,500 sheets) PK-510 Punch Kit SA-501 Scan Accelerator Kit SC-503 HDD Encryption Kit

DF-608 Reversing Automatic

# Available Print/Copy Functions\*

SD-503 Saddle Stitcher (for FS-514)

Account Track (up to 1,000 accounts) APS/AMS Auto Duplex Auto Reset Auto Tray Switching **Bi-Directional Communication** (Device Option Setting) B/W Public Access: /Password Protected Color Access Color Modes & Functions: Auto Color/Full Color Black & White Mode Single Color Mode 2-Color Mode Color Adjustments (Brightness, Contrast, Saturation, Sharpness, Red, Green, Blue, Portrait, Hue Density, Color Balance, Copy Density) Sample Copy

#### **Available Print/Copy Functions** Continued\*

Copy Modes (Simplex/Duplex, 2-in-1, 4-in-1, 8-in-1, Book Separation, **Booklet Creation, Catalog Binding)** Cover Mode

Creative Functions (Mirror Image, Image Repeat, XY Zoom, Image Centering, Base Color, Negative/Positive Reverse)

Criss-Cross Sorting

**Distribution Number Printing Energy Save Mode** 

**Enlarge Display** Erase (Frame, Book Frame, Book Center) Finishing (Group, Sort, Staple, Punch,

Booklet, Center-Fold, Crease Fold, Center-Staple)

Form Overlay **HDD Random Erase** Image Adjustments (Color Matching,

Pure Black Auto ON/OFF, Color Balance, Screen Setting, Image Smoothing ON/OFF)

Image Density Adjustment (Background: Manual/Auto; Density: Manual) Image Preview (Job Finishing Image Display, Engine Configuration Display)

Job Erase Job List

Job Reserve LDAP/up to 5 LDAP Servers/Global LDAP

OHP Interleaving Mixplex, Mix-Media

Paper Type Selection (Normal, Thick 1, Thick 2, Thick 3, OHP)

Program/Recall Jobs

Proof

Secure Printing

Separate Scan

Sleep Mode

Text Enhancement Adjustment User Authentication (Synchronize with Account Track)

User Box Function (Store Copy Jobs/Print Jobs/Scans/Fax Data, Print Stored Data, Route Scanned Data, Print or Combine Scanned Data)

Utility (Meter Count, Environment Setting, Default Setting, One-Touch Setting, Check Consumable Life, Admin Mode)

Watermarks Zoom Selection (AMS, Fixed Zoom Ratio, User Programmable Zoom

Ratio, Manual)

**Available Scan Functions\*** 

Scan-to-Email Scan-to-FTP

Scan-to-SMB (Scan-to-Desktop) Scan-to-HDD (Scan-to-User Box)

Network TWAIN

Available Fax Functions\*

**Auto Dialing** 

Auto Memory Reception Auto Reduction Printing

Border Erase Transmission

Broadcasting (maximum 600 locations)

**Bulletin Board** 

**Density Adjustment** 

**Duplex Transmission/Reception** Exposure Mode (Text, Text/Photo,

Photo, Dot Matrix)

Fax Forwarding

Image Rotation Transmission/Reception

Internet Faxing IP Address Faxing

Mailbox (Private)

Transmission/Reception

Memory/Quick Dial Memory Transmission/Reception

Mixed Originals Transmission

Original Size Designation Overseas Transmission

Password Transmission/Reception

PC Fax (PCL driver only) Polling Transmission/Reception

**Priority Transmission** 

Program Dialing: 400 programs

Redial

Relay Broadcasting Relay Transmission

Remote Reception

TSI User Box

TSI User Box Routing

Secure Printing

Timer Transmission

**Emperon Print System** 

PROCESSOR:

600 MHz (PPC750FX)

RAM:

512 MB (standard)

HARD DISK DRIVE:

40 GB (standard copier memory)

PAGE DESCRIPTION LANGUAGE:

PCL 5e/5c Emulation PCL6 (XL version 2.1) Emulation PS3 Emulation

FONTS:

PCL Resident Fonts: 80 outline + 1 bitmap PS3 Emulation Resident Fonts: 136 outline

PRINT DRIVERS:

PCL6: Windows 98SE, ME, 2000, XP, 2003, NT 4.0 SP6 PS3: Windows 98SE/ME (PPD file), 2000/XP/2003/NT 4.0 SP6 (Print Drivers). Mac OS 9.2 or later, Mac OS X 10.2, Mac OS X 10.3, and Mac OS x 10.4 (PPD files) TWAIN Driver: Windows 98SE, ME,

INTERFACE:

Ethernet 10/100 BaseT Parallel IEEE 1284 (optional) USB 1.1, 2.0 (optional)

2000, XP, NT 4.0 SP6

PROTOCOLS:

TCP/IP, IPX/SPX (NDS), SMB, NetBEUI, LPD, LPR, IPP 1.1, SNMP, HTTP, AppleTalk (EtherTalk), Pserver (Novell 4.x, 5, 6/NDS), NPrinter, NDPS, SMTP, POP3, LDAP, SSL

PAGESCOPE APPLICATIONS:

Network & Device Management (bundle): HDD Backup Tool PageScope Box Operator PageScope Data Administrator PageScope Direct Print PageScope EMS Plug-Ins PageScope Job Spooler PageScope NDPS Gateway

PageScope Net Care PageScope Network Setup PageScope Print Status Notifier PageScope Web Connection

OPTIONAL SOFTWARE:

PageScope Workware PageScope Router

OTHER UTILITIES:

Plug-in for HP Web JetAdmin

Fiery® IC-406 Embedded Image Controller (option)\*

PROCESSOR: Intel® Celeron® 2.0 GHz

**OPERATING SYSTEM:** Linux

HARD DISK DRIVE: 80 GB

MEMORY: 256 MB (standard); 512 MB (maximum)

PAGE DESCRIPTION LANGUAGE:

PCL 6, Adobe PostScript 3 (3017)

FONTS: PostScript Fonts: 136,

PCL Fonts: 80

PRINT DRIVERS:

Windows 98, 2000, 2003 XP, NT 4.0

Mac OS 8.6, 9.x

Mac OS X 10.1 and 10.2 (Classic mode) Mac OS X 10.2.4 and later (Native mode)

INTERFACE: 10/100 BaseT, RJ45, USB 2.0

PROTOCOLS:

TCP/IP (Static IP, Auto IP, DHCP/BOOTP), LPR, SMB, IPX/SPX (NDS), AppleTalk (EtherTalk), HTTP, SNMP, IPP, Port 9100, SMTP, POP3, LDAP, SSL/TLS

UTILITIES:

ColorWise® Pro Tools 3.7 Command Workstation™ 4.2 (for Windows) Command Workstation $^{\mathsf{TM}}$  LE (for Mac OS 10.2.4 and later) Fiery® Downloader™ Fiery® Spooler™ Fiery® WebTools™ 3.0 Standard Spot-On Color Matching

OPTIONS:

256 MB Memory (upgrade, IC-406) 256 MB Memory (Banner Printing; Upgrade, Engine) EFI Impose (v. 2.6) EFI Densitometer (ED-100) Graphic Arts Options: Hot Folders, Auto Trapping EFI Color Profiler Kit (ES-1000) (Spectrophotometer with monitor profiling software) **EFI Secure Erase** 



<sup>\*</sup> Some functions may require options, which may or may not be available at time of launch.