KONICA MINOLTA

bizhubC352P

CONNECT_   COMMUNICATE_   CONTROL_

PRINT
FAX + COPY
SCAN

GENERAL SPECIFICATIONS:

TYPE:
Full-Color Printer

PRINT PROCESS:
Tandem Process

IMAGING SYSTEM:
Simitri® Color Polymerized Toner
Error Diffusion Method

MONTHLY DUTY CYCLE:
100,000 pages

PRINT/COPY SPEED:
Full Color and B&W: 35 ppm (letter, portrait)

PRINT RESOLUTION:
1800 dpi Equivalent x 600 dpi

MEMORY:
512 MB (standard/maximum)

HARD DISK DRIVE:
40 GB (optional)

GRADATION:
256 color shades per pixel

PAPER SIZE:
Multi-Purpose Cassette: 4" x 6" to
12" x 18"
Universal Cassette: 5-1/2" x 8-1/2" to
11" x 17"
Multiple Bypass: 4" x 6" to 12" x 18"

WARM-UP TIME:
Less than 72 seconds

FIRST PRINT:
Full color: less than 8.5 seconds (letter)
B&W: less than 6.5 seconds (letter)

PRINT QUANTITY:
1 - 999

COLOR MODES:
Auto Color, Full Color, Black & White,
2-Color, Single Color

STANDARD PAPER SUPPLY:
250-sheet multi-purpose cassette
(16 lb. bond to 140 lb. index)
500-sheet cassette
(16 lb. bond to 24 lb. bond)
100-sheet bypass
(16 lb. bond to 140 lb. index)

MAXIMUM PAPER CAPACITY:
3,350 sheets (total, with options)

POWER REQUIREMENTS:
120 V, 60 Hz

POWER CONSUMPTION:
Less than 1.5 kW

DIMENSIONS (W x D x H):
C352P: 25-1/2" x 28" x 23-3/4"
(standard configuration)

WEIGHT:
C352P: 178 - 1/2 lbs.

OPTIONS:
DK-502 Copy Desk
EK-702 Parallel/USB 2.0 I/F Kit
MK-706 Enhanced Option Connection
FS-514 Base Finisher
MT-501 Mail Bin Kit
OT-601 Output Tray
PK-510 Punch Kit
SD-503 Saddle Stitcher
SC-503 HDD Encryption Kit
PC-103 Paper Feed Cabinet
(500 sheets)
PC-203 Paper Feed Cabinet
(500 sheets x 2)
PC-403 Large Capacity Tray
(2,500 sheets)

Available Print Functions*

Account Track (up to 1,000 accounts)
Auto Duplex
Auto Reset
Auto Tray Switching
Bi-Directional Communication
(Device Option Setting)

Color Modes & Functions:
  Auto Color/Full Color
  Black & White Mode
  Single Color Mode
  2-Color Mode
  Color Adjustments (Brightness,
  Contrast, Saturation, Sharpness,
  Red, Green, Blue, Portrait, Hue Density,
  Color Balance, Copy Density)
Criss-Cross Sorting
Distribution Number Printing
Energy Save Mode
Enlarge Display
Finishing (Group, Sort, Staple, Punch,
  Booklet, Center-Fold, Center-Staple)
Form Overlay
HDD Random Erase
Image Adjustments (Color Matching,
  Pure Black Auto ON/OFF, Color
  Balance,Screen Setting, Image
  Smoothing ON/OFF)
Image Density Adjustment (Background:
Image Preview (Job Finishing Image
  Display, Engine Configuration Display)
Job Erase
OHP Interleaving
Mixplex, Mix-Media
Paper Type Selection (Normal, Thick 1,
  Thick 2, Thick 3, OHP)
Proof Print
Secure Printing
Sleep Mode / Low Power
User Authentication (Synchronize with
Account Track)
User Box Function (Store Print Jobs
/Print Stored Jobs)
Watermarks

Emperon Print System

PROCESSOR:
600 MHz (PPC750FX)

RAM:
512 MB (standard)

HARD DISK DRIVE:
40 GB (standard copier memory)

PAGE DESCRIPTION LANGUAGE:
PCL 5e/5c Emulation
PCL6 (XL version 2.1) Emulation
PS3 Emulation

FONTS:
PCL Resident Fonts:
  80 outline + 1 bitmap
PS3 Emulation Resident Fonts:
  136 outline

PRINT DRIVERS:
PCL6: Windows 98SE, ME, 2000,
XP, 2003, NT 4.0 SP6
PS3: Windows 98SE/ME (PPD file),
2000/XP/2003/NT 4.0 SP6 (Print
Drivers), Mac OS 9.2 or later,
Mac OS X 10.2,
Mac OS X 10.3, and
Mac OS X 10.4 (PPD files)
TWAIN Driver: Windows 98SE, ME,
2000, XP, NT 4.0 SP6

INTERFACE:
Ethernet 10/100 BaseT
Parallel IEEE 1284 (optional)
USB 1.1, 2.0 (optional)

PROTOCOLS:
TCP/IP, IPX/SPX (NDS), SMB, NetBEUI,
LPD, LPR, IPP 1.1, SNMP, HTTP,
AppleTalk (EtherTalk), Pserver
(Novell 4.x, 5, 6/NDS), NPrinter,
NDPS, SMTP, POP3, LDAP, SSL

PAGESCOPE APPLICATIONS:
Network & Device Management (bundle):
  HDD Backup Tool
  PageScope Data Administrator
  PageScope Direct Print
  PageScope EMS Plug-Ins
  PageScope Job Spooler
  PageScope NDPS Gateway
  PageScope Net Care
  PageScope Print Status Notifier
  PageScope Network Setup
  PageScope Web Connection

OPTIONAL SOFTWARE:
PageScope Router

OTHER UTILITIES:
Plug-in for HP Web JetAdmin

KONICA MINOLTA

* Some functions may require options, which may or may not be available at time of launch.